


Full View Sight Flow Indicator



Product Description & Features:

- ❖ Sight Flow Indicator is used to observe inline flow of various Fluids
- ❖ The Model has been designed to enhance the visibility of fluid as they pass through the glass.
- ❖ Full 360° Viewing area to material flow through a line, which save time & energy
- ❖ It can be used in Vertical as well as Horizontal installation
- ❖ Max. Operating Temperature: 180° with PTFE Sealing
- ❖ Hydraulic Test Pressure: 5 Kg/cm²
- ❖ Standard Material of Construction: SS304 / 316
- ❖ All Wetted Parts are Glass & PTFE
- ❖ Flange Drilling: ASA150# / BS 10 Table F / E or as per requirement.

Material of Construction:

Part No.	Part List	Standard Materials
01	Flange	SS304 / SS316
02	Glass Tube	Annealed Borosilicate
03	Check Nut	SS202 / SS304 / SS316
04	Stud	SS202/304 / SS316
05	Bush & Packing	PTFE
06	Allan Cap Bolt	SS202 / SS304 / SS316

Optional:

Optional material will be provided on request.
Glass Length: 100mm / 150mm Available
T-Bush Teflon / washer available

Certification:

As per EN10204 3.1 B available on request

Guarantee / Warrantee:


"Taurus Engineering Industries" warrants its products as designed and manufactured to be free of defects in material and workmanship for period of 18 months from the date of dispatch or 12 month from the date of commissioning whichever is earlier, subject to the use in the manner as stated by Taurus.

Note: Due to continuous development program, the design and data given are subject to change without prior notice.

Manufacturer

TAURUS ENGINEERING INDUSTRIES

32, Libra Estate, B/h. Vallabhnagar School, GIDC, Odhav,
Ahmedabad-382415, Gujarat
Phone: 079-22871271, Telefax: 079-22870419,
E-mail: info.taurusengind@gmail.com
Web: www.taurusengind.in



Full View Sight Flow Indicator



Product Description & Features:

- ❖ Sight Flow Indicator is used to observe inline flow of various Fluids
- ❖ The Model has been designed to enhance the visibility of fluid as they pass through the glass.
- ❖ Full 360° Viewing area to material flow through a line, which save time & energy
- ❖ It can be used in Vertical as well as Horizontal installation
- ❖ Max. Operating Temperature: 180° with PTFE Sealing
- ❖ Hydraulic Test Pressure: 5 Kg/cm²
- ❖ Standard Material of Construction: Mild Steel
- ❖ All Wetted Parts are Glass & PTFE
- ❖ Flange Drilling: ASA150# / BS 10 Table F / E or as per requirement.

Material of Construction:

Part No.	Part List	Standard Materials
01	Flange	M.S.
02	Glass Tube	Annealed Borosilicate
03	Check Nut	M.S.
04	Stud	M.S.
05	Packing	PTFE
06	Allan Cap Bolt	M.S.

Optional:

Optional material will be provided on request.
Glass Length: 100mm / 150mm Available
T-Bush Teflon / washer available

Certification:

As per EN10204 3.1 B available on request

Guarantee / Warrantee:

"Taurus Engineering Industries" warrants its products as designed and manufactured to be free of defects in material and workmanship for period of 18 months from the date of dispatch or 12 month from the date of commissioning whichever is earlier, subject to the use in the manner as stated by Taurus.

Note: Due to continuous development program, the design and data given are subject to change without prior notice.

Manufacturer

TAURUS ENGINEERING INDUSTRIES

32, Libra Estate, B/h. Vallabhnagar School, GIDC, Odhav,
Ahmedabad-382415, Gujarat
Phone: 079-22871271, Telefax: 079-22870419,
E-mail: info.taurusengind@gmail.com
Web: www.taurusengind.in

